

megamount 751XL Truck tire changer

The ideal heavy duty tyre changer for big tyres



Electro hydraulic tyre changer for big tube and tubeless tyres

That is self-evident for us:

- Portable control centre
- Movable head tool carriage
- 2 speed chuck rotating system
- Adjustable working pressure
- Clamping range 14 - 46 inches (option -56")
- Tyre diameter maximal 1065 mm
- Tyre diameter maximal 2300 mm

For all problems the right solution:



CLAMPING DEVICE

The hydraulic pressure of the rim clamping can be adjusted to avoid any damage of the rim.



DOUBLE MOUNTING HEAD

The double mounting/demounting tool allows an operation with tube and tubeless tyres

CONTROL UNIT

The chuck can be turned with 2 speeds. This allows a flexible and smooth handling of all tyre dimensions. The control unit can be moved to allow an operation in the most suitable position.



This comes with the machine



Technical Data	
Clamping Range	14"-56" (standard -46"/option -56")
Max. wheel weight	1500 kg
Max. wheel diameter	2300 mm (90½")
Max. wheel width	1065 mm (42")
Hydraulic pump motor	1,1 kw 400 v-3PH
Gearbox motor	1,2 – 1,8 kw 400 v-3PH
Operating pressure	0 - 130 bar
Bead breaker force inside-outside	2690 kg
Noise level in working condition	< 70 db
Net weight	770 kg

Dimensions

